

**CLAIM AMENDMENTS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-25. (cancelled)

26. (previously presented) A method of receiving video signals from a plurality of video cameras wherein the method comprises steps of:

- a. selecting one of the plurality of video cameras for providing a video signal to a video decoder;
- b. retrieving a parameter representative of the video signal from a memory store; and
- c. conditioning the video decoder according to the parameter; and
- d. updating the parameter according to the video signal thereby forming an updated parameter and a predicted value for the parameter,

wherein forming the predicted value for the parameter includes calculating a difference between prior value obtained for the parameter and a current value obtained for the parameter and combining the difference with the current value.

27. (original) The method according to claim 26 further comprising a step of capturing a video frame from the selected one of the plurality of video cameras.

28. (original) The method according to claim 27 further comprising a step of storing the captured video frame.

29. (original) The method according to claim 27 further comprising a step of completing a cycle wherein the step of completing the cycle comprises performing the steps of selecting, retrieving, conditioning and capturing for each camera of the plurality.

30-32. (canceled)

33. (previously presented) The method according to claim 26 further comprising a step of storing the updated parameter in association with an identification of the selected one of the plurality of video cameras.
34. (original) The method according to claim 33 further comprising a step of selecting a next one of the plurality of cameras according to a sequence.
35. (previously presented) The method according to claim 26 further comprising a step of storing the updated parameter in a storage location which is associated with the corresponding camera.
36. (original) The method according to claim 35 further comprising a step of selecting a next one of the plurality of cameras according to a sequence.
37. (original) The method according to claim 26 further comprising a step of initializing the apparatus upon start-up by obtaining an initial value for the parameter corresponding to each video signal during a first cycle through all of the cameras wherein a video frame is captured from each camera during the first cycle.
38. (original) The method according to claim 26 further comprising a step of initializing the apparatus upon start-up by performing two or more cycles through all of the cameras and wherein a video frame is captured from each camera only upon completion of the two or more cycles.
39. (original) The method according to claim 26 wherein the parameter is a horizontal frequency of the video signal.
40. (original) The method according to claim 39 wherein the parameter is a horizontal phase of the video signal.
41. (original) The method according to claim 40 wherein the parameter is a chrominance frequency of the video signal.

42. (original) The method according to claim 41 wherein the parameter is a chrominance phase of the video signal.
43. (original) The method according to claim 26 wherein the parameter is a gain level for the video signal.
44. (original) The method according to claim 43 wherein the parameter is a dc clamping level for the video signal.